

ActiV Conventional Weatherproof Hi-Output 100dB(A) Wall Sounder (IP55)

Part No. BF430C/CC/DR/65



Overview

- Third-party certified to EN54-3 (Sounders).
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low)
- Alarm Current at 30Vdc = 5.5mA.
- Alarm Current at 18Vdc = 3.8mA.
- IP55C rated (weatherproof).
- Manufactured in the UK by C-TEC.





More Information

Technical Specifications

Approvals/certifications Certified to EN54-3 by the LPCB.

Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other Protocol/compatibility

makes (testing on third-party panels is recommended before use)

Application/operation Designed to be wall mounted. Weatherproof to IP55C.

VAD category & coverage N/A. Flash rate & colour N/A.



T 01942 322744 F 01942 829867

E sales@c-tec.co.uk

W www.c-tec.com

















Supply/operating voltage 18 to 30V DC. Nominal SPL (Sound Pressure Level) 100dB(A).

Alarm current At 30Vdc: 5.5mA; At 18Vdc: 3.8mA. Product dimensions (mm) 114mm diameter x 132mm deep.

IP Rating IP55C (Weatherproof).

Weight 315g.

Operating conditions/temperature -10 $^{\circ}$ C to +55 $^{\circ}$ C. Max. 95% RH (Non-condensing).















