

Compact W-3-3.1 Wall VAD c/w 91dB(A) Sounder

Part No. **BF451A/CX/SR**



Overview

- Third-party certified to EN54-3 (Sounders), EN54-23 (VADs) and 17 (Isolators) by Intertek.
- Provides 'W-3-3.1' light distribution when wall mounted (min 0.4 lux over a 3 x 8m cylindrical area).
- Can also provide 'C-3-8' light distribution when ceiling mounted (min. 0.4 lux over a 3 x 3.1m cuboid area).
- Impressive 91dB(A) sound output @ 1m.
- Onboard short-circuit loop isolator.
- 550µA quiescent current.
- 14mA alarm current @24V DC (VAD lit, sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP21C rated.



More Information

Technical Specifications

Approvals/certifications
Protocol/compatibility

Certified to EN54-3, 23 & 17 by Intertek.
Compatible with C-TEC's XFP/ZFP XP95/Discovery Addressable Fire Panels.



Application/operation	Provides W-3-2.1 coverage when wall mounted. Alternatively can be ceiling mounted to provide C-3-8 coverage.
VAD category & coverage	W-3-3.1 (30m3 cuboid coverage); C-3-8 (151m3 cylindrical coverage).
Flash rate & colour	0.5Hz / White.
Supply/operating voltage	17 to 28V DC (Sounder); 21 to 28V DC (Sounder/VAD).
Quiescent current	550µA @ 24 VDC.
Nominal SPL (Sound Pressure Level)	91dB(A) when set to tone 1.
Alarm current	14mA (VAD lit, Sounder on max).
Indicators	Polling (green LED) & Short Circuit Isolator Active (amber LED).
Product dimensions (mm)	102mm diameter x 63mm deep.
IP Rating	IP21C (Type A).
Weight	175g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom