

## Certificate of Product Approval

Certificate Number: 330s

Issue: 03

### Zeta Alarms Limited

Detection House  
72-78 Morfa Road  
Swansea  
SA1 2EN  
United Kingdom



is certified by BRE **Global** Ltd. and is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirement(s) of the standards as detailed below:

#### Products

##### Audible Warning Devices

ZXTB/R  
ZXTB/W  
ZRPB/R  
ZRPB/W  
MKII-AXTB/R  
MKII-AXTB/W  
ZRAPB/R  
ZRAPB/W

(refer to Appendix for details)

#### Standards

**EN 54-3:2001 + A1:2002 + A2:2006**  
**EN 54-23:2010**

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

Signed for BRE Global Ltd

P Halligan

Verifier

16 January 2018

Date of Issue

17 June 2016

Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)  
LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 330s

Issue: 03

### Zeta Alarms Limited

Certified Product	Description	LPCB Ref.No.
ZXTB/R	Conventional Xtratone Indoor Sounder Beacon, Red Plastic, White Flash Notes: 1. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 7: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 2. The wall mounted, Type A VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.4 – 7.0 - Flash rate 0.5Hz - White LED	330s/01
ZXTB/W	Conventional Xtratone Indoor Sounder Beacon, White Plastic, White Flash Notes: 1. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 7: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 2. The wall mounted, Type A VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.4 – 7.0 - Flash rate 0.5Hz - White LED	330s/02

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

  
Signed for BRE Global Ltd

P Halligan  
Verifier

16 January 2018  
Date of Issue

17 June 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)  
LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 330s

Issue: 03

### Zeta Alarms Limited

Certified Product	Description	LPCB Ref.No.
ZRPB/R	<p>Conventional Raptor Outdoor Sounder Beacon, Red Plastic, White Flash</p> <p>Notes:</p> <ol style="list-style-type: none"> <li>Meets the requirements of EN 54-3 at the following tones:               <ul style="list-style-type: none"> <li>Tone 0: 800Hz and 970Hz, 500ms each</li> <li>Tone 7: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop</li> </ul> </li> <li>The wall mounted, Type B VAD meets the requirements of EN 54-23 for the following:               <ul style="list-style-type: none"> <li>Coverage volume W 5.1 – 7.25</li> <li>Flash rate 0.5Hz</li> <li>White LED</li> </ul> </li> </ol>	330s/03
ZRPB/W	<p>Conventional Raptor Outdoor Sounder Beacon, White Plastic, White Flash</p> <p>Notes:</p> <ol style="list-style-type: none"> <li>Meets the requirements of EN 54-3 at the following tones:               <ul style="list-style-type: none"> <li>Tone 0: 800Hz and 970Hz, 500ms each</li> <li>Tone 7: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop</li> </ul> </li> <li>The wall mounted, Type B VAD meets the requirements of EN 54-23 for the following:               <ul style="list-style-type: none"> <li>Coverage volume W 5.1 – 7.25</li> <li>Flash rate 0.5Hz</li> <li>White LED</li> </ul> </li> </ol>	330s/04

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

  
Signed for BRE Global Ltd

P Halligan  
Verifier

16 January 2018  
Date of Issue

17 June 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)  
LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 330s

Issue: 03

### Zeta Alarms Limited

Certified Product	Description	LPCB Ref.No.
MKII-AXTB/R	Zeta Addressable Xtratone Type A Wall Sounder Beacon, Red Plastic, White Flash Notes: 1. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 8: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 2. The wall mounted, Type A VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.1 – 9.1 - Flash rate 0.5Hz - White LED	330s/05
MKII-AXTB/W	Zeta Addressable Xtratone Type A Wall Sounder Beacon, White Plastic, White Flash Notes: 1. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 8: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 2. The wall mounted, Type A VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.1 –9.1 - Flash rate 0.5Hz - White LED	330s/06

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.



Signed for BRE Global Ltd

P Halligan  
Verifier

16 January 2018  
Date of Issue

17 June 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)  
LPCB is a Registered Trademark of the Building Research Establishment Ltd.




## Appendix to Certificate No: 330s Zeta Alarms Limited

Issue: 03

Certified Product	Description	LPCB Ref.No.
ZRAPB/R	Zeta Addressable Raptor Type B Sounder Beacon, Red Plastic, White Flash Notes: 1. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 8: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 2. The wall mounted, Type B VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.0 – 8.7 - Flash rate 0.5Hz - White LED	330s/07
ZRAPB/W	Zeta Addressable Raptor Type B Sounder Beacon, White Plastic, White Flash Notes: 3. Meets the requirements of EN 54-3 at the following tones: - Tone 0: 800Hz and 970Hz, 500ms each - Tone 8: 500 to 1200Hz -3.5s sweep, 0.5 s silence, repeat Dutch Slow Whoop 4. The wall mounted, Type B VAD meets the requirements of EN 54-23 for the following: - Coverage volume W 3.0 – 8.7 - Flash rate 0.5Hz - White LED	330s/08

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

  
Signed for BRE Global Ltd

P Halligan  
Verifier

16 January 2018  
Date of Issue

17 June 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)  
LPCB is a Registered Trademark of the Building Research Establishment Ltd.



**bre**