


## **CONCORD**

# CONCORD LED Exit Sign, Surface Mount, IP40, Maintained/non-maintained, 3.6V NiCD Battery





















#### **GENERAL DATA**

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White
Material	Polycarbonate
IP Rating	IP40
IK Rating	IKO8
Mounting Type	Surface
Warranty (Years)	3
Life Time Hours	50,000

#### **DIMENSIONS & WEIGHT**

#### **BLE LIGHTING AND POWER LTD**



Length (mm)	297
Width (mm)	206
Depth (mm)	40
Weight (g)	830
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	1.3
Classification	Class II
Operating Temperature (°C)	0 to +40
Power Factor	0.59
OPTICAL	
Colour Temperature	6000K
CRI	80
Viewing Distance (M)	25
EMERGENCY	
Battery Type	NiCD 3.6V
Battery Capacity	1.5Ah
Battery Warranty (Years)	1
Recharge Time (hrs)	24
Battery Replaceable	Yes
Mode of Operation	Maintained / Non-maintained
Test Procedure	Manual
Emergency Duration (hrs)	3
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL

### **PACKAGING**

#### **BLE LIGHTING AND POWER LTD**

## DATA SHEET EL-131701



Packaging Length (mm)	315
Packaging Width (mm)	210
Packaging Depth (mm)	46

#### **BLE LIGHTING AND POWER LTD**