


FIRTH

FIRTH LED Slimline Emergency Exit Box, 3.2V LiFePO4 Battery, Self Test























GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White
Material	Polycarbonate
IP Rating	IP40
IK Rating	IKO8
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50,000
DIMENSIONS & WEIGHT	

Length (mm)	320
Width (mm)	26
Height (mm)	185
Weight (g)	616

BLE LIGHTING AND POWER LTD



ELECTRICAL

ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	3.5
Classification	Class I
Operating Temperature (°C)	0 to +40
Power Factor	0.28
OPTICAL	
Colour Temperature	6500K
CRI	70
Beam Angle (°)	100.5
Lumen Output Mains (lm)	55
Viewing Distance (M)	29
EMERGENCY	
Battery Type	LiFePO4 18650 3.2V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	Yes
Mode of Operation	Maintained / Non-maintained
Test Procedure	Self Test
Emergency Duration (hrs)	3
Lumen Output Emergency (lm)	36
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL
PACKAGING	
Packaging Length (mm)	330

BLE LIGHTING AND POWER LTD

DATA SHEET EL-131250



Packaging Width (mm)	195
Packaging Depth (mm)	35

BLE LIGHTING AND POWER LTD