


# **FOXHILL**

# FOXHILL High Output LED Emergency Bulkhead























### **GENERAL DATA**

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White
Material	Polycarbonate
Diffuser Type	Prismatic
Diffuser Material	Polycarbonate
IP Rating	IP65
IK Rating	IKO8
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50000

### **DIMENSIONS & WEIGHT**

#### **BLE LIGHTING AND POWER LTD**




Langth (mm)	321		
Length (mm)			
Width (mm)	167		
Depth (mm)	83		
Weight (g)	1454		
ELECTRICAL			
Input Voltage (V)	220-240		
Input Frequency (Hz)	50		
Wattage (W)	10		
Classification	Class II		
Operating Temperature (°C)	+5 to +45		
Power Factor	0.3		
OPTICAL			
Colour Temperature	6500		
CRI	80		
Beam Angle (°)	135		
EMERGENCY			
Battery Type	LiFePO4 6.4V		
Battery Capacity	6.6		
Battery Warranty (Years)	5		
Recharge Time (hrs)	24		
Battery Replaceable	Yes		
Mode of Operation	Non-maintained		
Test Procedure	Manual		
Emergency Duration (hrs)	3		
Lumen Output Emergency (lm)	1000/1500		
STANDARDS & APPROVALS			
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22		
CE Mark	Yes		
UKCA Mark	Yes		
WEEE Symbol	Yes		
Accredited Members	ISO 9001, LIA, ICEL		

#### **BLE LIGHTING AND POWER LTD**



## **Spacing Tables**



	OPEN (ANTI-PANIC) AREA (0.5 LUX MINIMUM)				
at 1587lm	<b>*</b>		<b>+</b>	<del>\</del>	
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
3.0m	7.4	17.3	9.6	22.8	
4.0m	8.3	19.7	10.7	25.9	
6.0m	9.9	23.2	12.5	30.7	