


HEATHLANDS

HEATHLANDS Dali Emergency Downlight, IP20, Non-maintained, LiFePO4





















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL9016
Material	Polycarbonate
IP Rating	IP20
IK Rating	IK07
Mounting Type	Recessed. Outer ring supplied for larger cut outs
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Depth (mm)	32
Diameter (mm)	55
Cut out (mm)	42-50

BLE LIGHTING AND POWER LTD



Weight (g)	325
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	3.5
Classification	Class II
Operating Temperature (°c)	0 to +45
Power Factor	0.2
OPTICAL	
Colour Temperature	5000K
CRI	>70
Beam Angle (°)	Open Area Lens: 140°, Corridor Lens: 160x40°
Lumen Output Mains (lm)	240lm
EMERGENCY	
Battery Type	LiFePO4 6.4V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	No
Mode Of Operation	Non-maintained
Test Procedure	Dali
Emergency Duration (Hrs)	3
Lumen Output Emergency (lm)	240lm
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, ISO 140001

BLE LIGHTING AND POWER LTD