


HEELEY

HEELEY LED Emergency Downlight, IP20, Non-maintained, Replaceable Lens, LiFePO4



















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL 9016
Material	Polycarbonate
IP Rating	IP20
IK Rating	IKO4
Mounting Type	Surface or Recessed
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Depth (mm) 34mm Recessed / 51mm Surface

BLE LIGHTING AND POWER LTD



Diameter (mm)	98
Cut Out (mm)	75-90
Weight (g)	137
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	2
Classification	Class II
Operating Temperature (°C)	+5 to +35
Power Factor	0.4
OPTICAL	
Colour Temperature	6500K
CRI	80
Beam Angle (º)	Horizontal: 145º / Vertical: 136º
EMERGENCY	
Battery Type	LiFePO4 3.2V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	No
Mode of Operation	Non-maintained
Test Procedure	Manual
Emergency Duration (hrs)	3
Lumen Output Emergency (lm)	150
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL

PACKAGING

BLE LIGHTING AND POWER LTD

DATA SHEET EL-153151



Packaging Length (mm)	101
Packaging Width (mm)	101
Packaging Depth (mm)	62

BLE LIGHTING AND POWER LTD