


KELHAM

KELHAM Dali Emergency Twin Spot, IP65, Non-maintained, LiFePO4





















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL9016
Material	Polycarbonate
IP Rating	IP65
IK Rating	IK06
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Length (mm) 267

BLE LIGHTING AND POWER LTD



Width (mm)	260
Depth (mm)	64
Weight (g)	965
ELECTRICAL	
	220-240
Input Voltage (V)	
Input Frequency (Hz)	50
Wattage (W)	9W
Classification	Class II
Operating Temperature (°c)	0 to +45
Power Factor	0.3
OPTICAL	
Colour Temperature	5000K
CRI	>80
Beam Angle (°)	110
Lumen Output Mains (lm)	1200lm
EMERGENCY	
Battery Type	LiFePO4 6.4V
Battery Capacity	6.0Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	No
Mode Of Operation	Non-maintained
Test Procedure	Dali
Emergency Duration (Hrs)	3
Lumen Output Emergency (lm)	1200lm
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, ISO 14001

BLE LIGHTING AND POWER LTD



BLE LIGHTING AND POWER LTD