


KIRKSTONE

KIRKSTONE LED Emergency Downlight, IP20, Non-maintained, Replaceable Lens, LiFePO4



















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL 9016
Material	Polycarbonate
IP Rating	IP20
IK Rating	IKO4
Mounting Type	Recessed
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Depth (mm)	78
Diameter (mm)	61
Cut out (mm)	42-56

BLE LIGHTING AND POWER LTD



Weight (g)	194
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	3
Classification	Class II
Operating Temperature (°c)	5 to +35
Power Factor	0.45
OPTICAL	45004
Colour Temperature	6500K
CRI	80
Beam Angle (°)	Horizontal: 146º / Vertical: 148º
EMERGENCY	
Battery Type	LiFePO4 3.2V
Battery Capacity	3.OAh
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	Yes
Mode Of Operation	Non-maintained
Test Procedure	Manual
Emergency Duration (Hrs)	3
Lumen Output Emergency (lm)	250
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, ISO 14001
	·
PACKAGING	1.45
Packaging Length (mm)	145
Packaging Width (mm)	100

BLE LIGHTING AND POWER LTD

DATA SHEET EL

EL-155350



Packaging Depth (mm)

45

BLE LIGHTING AND POWER LTD