


RUSKIN

RUSKIN LED Emergency Bulkhead, IP65, Maintained/non-maintained, LiFePO4 Battery





















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL 9016
Material	Polycarbonate
Diffuser Type	Prismatic
Diffuser Material	Polycarbonate
IP Rating	IP65
IK Rating	IK07
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Length (mm)	357
Width (mm)	116
Depth (mm)	50
Weight (g)	475

ELECTRICAL

BLE LIGHTING AND POWER LTD



Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	4.5
Classification	Class II
	+5 to +35
Operating Temperature (°C) Power Factor	0.4
- Tower racion	0.4
OPTICAL	
Colour Temperature	5700-6500K
CRI	80
Beam Angle (°)	120
Lumen Output Mains (lm)	150
EMERGENCY	
Battery Type	LiFePO4 3.2V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	No
Mode of Operation	Maintained / Non-maintained
Test Procedure	Manual
Emergency Duration (hrs)	3
Lumen Output Emergency (lm)	150
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL
PACKAGING	
Packaging Length (mm)	360
Packaging Width (mm)	120
Packaging Depth (mm)	64

BLE LIGHTING AND POWER LTD



BLE LIGHTING AND POWER LTD