


STANNINGTON

STANNINGTON LED Emergency Twin Spot with Self Test, IP65, LiFePO4 Battery, Self Test





















GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White
Material	Polycarbonate
IP Rating	IP65
IK Rating	IKO8
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Length (mm) 290

BLE LIGHTING AND POWER LTD



Width (mm)	300
Depth (mm)	46
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	3
Classification	Class II
Operating Temperature (°C)	+5 to +45
Power Factor	0.4
OPTICAL	
Colour Temperature	6500K
CRI	80
Beam Angle (°)	110
EMERGENCY	1.5.004220
Battery Type	LiFePO4 3.2V
Battery Capacity	3.6Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	No
Mode of Operation	Maintained / Non-maintained
Test Procedure	Self Test
Emergency Duration (hrs)	3
Lumen Output Emergency (lm)	400
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, ISO 14001
PACKAGING	
Packaging Length (mm)	317

BLE LIGHTING AND POWER LTD

DATA SHEET EL-142251



Packaging Width (mm)	295
Packaging Depth (mm)	52

BLE LIGHTING AND POWER LTD