

TM1

A single-channel surface-mounted programmer facilitates the operation of vents by setting their operation time (open and closed). It has a display which makes it even more useful. may be switched off on the switch.



Application



Natural
Ventilation

Part Codes

TM1	TM1 Digital Timer
-----	-------------------

Technical Data

Primary Voltage	230V AC, 3A
Operating Condition	0°C - +50°C
Size	120 x 98 x 27mm
Protection Type	IP 30
Delivery	1 x Digital Timer
Cable Size	5-Core

Compatible With

SCP-500	SCP500 Control Unit 24V 5 Amp
SCP-800	SCP800 Control Unit 24V 8 Amp
WCC 103	WCC 103 Control Unit 24V 3 Amp
WCC 103A	WCC 103 Control Unit 24V 3 Amp - Bluetooth
WCC 106A	WCC 103 Control Unit 24V 6 Amp - Bluetooth
WCC 310/320	WCC 310/320 Control Unit 24V 10 Amp / 20 Amp
WCC 310/320-PLUS	WCC 310/320 PLUS Control Unit 24V 10 Amp / 20 Amp
WSC 310/320-PLUS	WSC 310/320 PLUS Control Unit 24V 10 Amp / 20 Amp
WSC 520/540/560	WSC 520/540/560 Control Unit 24V 20 Amp / 40 Amp / 60 Amp