



TUNWELL

TUNWELL Dali Emergency Exit Sign, Maintained / Non-maintained, IP20, LiFePO4























GENERAL DATA

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White RAL9016
Material	Polycarbonate
IP Rating	IP20
IK Rating	IK06
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	50,000

DIMENSIONS & WEIGHT

Length (mm) 330

BLE LIGHTING AND POWER LTD



Width (mm)	192
Depth (mm)	47
Weight (g)	655
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	2-5W
Classification	Class II
Operating Temperature (°c)	0 to +45
Power Factor	>0.3
OPTICAL	
Colour Temperature	6000K
CRI	>80
Beam Angle (°)	130
Lumen Output Mains (Im)	50lm
Viewing Distance (M)	30M
Viewing Disidirce (M)	30101
EMERGENCY	
Battery Type	LiFePO4 3.2V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Mode Of Operation	Maintained / Non-maintained
Test Procedure	Dali
Emergency Duration (Hrs)	3
Lumen Output Emergency (lm)	50lm
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, ISO 14001

BLE LIGHTING AND POWER LTD



BLE LIGHTING AND POWER LTD