

CPS-P1-040-0202-B



Performance features

- + Compact SHEV control panel especially for high-current applications
- + Up to 20 A current consumption per group
- + Up to 16 SHEV control panels can be interconnected via the main/sub network (not with design CPS-P1-xxx-xxxx-B)
- + Stabilised output voltage
- + Configuration can be carried out without software via DIP switches
- + Additional functions via the integrated expansion interface (not with design CPS-P1-xxx-xxxx-B)
- + Connection of up to 8 SHEV operation panels and 14 fire detectors per line (Only detectors permitted by D+H may be used)
- + Min. 72 hr battery backup supply

Approvals / Certificates

Details of approval on request.



G 525002



0786-CPR-50690



5014068.Z5001

Technical data

CPS-P1-040-0202-B

Supply	230 V AC / 50 Hz / 1010 VA
Stand-by power	< 6 W
Output	24 V DC / 40 A
Ripple	< 0,5 Vss
Mode of operation monitoring	Continuous duty
Mode of operation alarm / ventilation	Short-time duty 30 % duty cycle
Type of protection	IP 54
Temperature range	-5 °C ... +40 °C
Line / Group	2 / 2
Housing	Plastic
Colour	Light grey (~ RAL 7035)
W x H x D	400 x 500 x 245 mm
Battery type	Typ 5 (2x)
Weight	8.7 kg
Art. No.	30.120.16

Example of application

